



M15-22A-K-PP

1.000 - 3.000 l/h Cartridges

Typical applications

Plating and process industry

Features

- Magnetic drive pump
- Filter chamber with welded bottom (no seal)
- One or two filter chambers (parallel or serial)
- String wound, spunbonded, pleated or carbon cartridges
- All PP or PVDF construction
- Max. temperature PP 80°C / PVDF 100°C
- Unions for rigid piping (PP, PVDF or CPVC sockets)
- Standard with 3 phase motor, thermal overload switch, lead without plug, air release and drain valve

Options

- Hose connection
- Pressure gauge
- Single phase motor
- Single open end cartridges



M10-11A-K-PP

Filter Systems series 1

 www.hendor.com

Pump	l/h	kW*	Union (d/DN) InOut		Hose InOut		Type	Chamber	Medium	Material
Magnetic drive	1000	0,12	32/25	25/20	1"1"	M10	11A	K	PP-EPDM PVDF-Viton	
	2000	0,18			1"1"	M11	12A			
	3000	0,18			1¼"1"	M15	21A(S)			
							22A(S)			
				Selection:	M15	22A	K	PP		

* For 3-phase motors < 220V the indicated motor will be one size bigger.

K = cartridges

Qty x L

11A-K = 1 x 10"

12A-K = 1 x 20"



Parallel filtration

Qty x L

21A-K = 2 x 10"

22A-K = 2 x 20"



Serial filtration

Qty x L

21AS-K = 2 x 10"

22AS-K = 2 x 20"