



M220-232A-K-PP

20.000 - 35.000 l/h Cartridges

Typical applications

Plating and process industry

Features

- Service friendly, ideal cleaning access height
- Magnetic drive or mechanical seal pump
- Filter chamber with welded bottom (no seal)
- DOE cartridges
- All PP construction, max. temperature PP 80°C
- Unions for rigid piping (PP, PVDF or CPVC sockets)
- Standard with 3 phase motor, thermal overload switch, lead without plug, pressure gauge, air release and drain valve

Options

- Hose connection, dry run protection, contact manometer
- By pass with flowmeter
- Single open end cartridges

Filter Systems series 23

 www.hendor.com

Pump	l/h	kW	Union (d/DN)		Hose		Type ¹⁾	Chamber ²⁾	Medium	Slurrytank	Material
			In	Out	In	Out					
Magnetic drive	20000	2,2					M220				
	26000	3	63/50	63/50	2 1/2"	2 1/2"	M300				
	35000	4					M400				
Mechanical seal	24000	2,2					S220	232A	K	S	PP-EPDM
	32000	3	63/50	63/50	2 1/2"	2 1/2"	S300				
Selection:							M220	232A	K	S	PP

K = cartridges



Qty x L

232A-K = 23 x 20"