



MX40-32A-P-S-PP

3.000 - 4.000 l/h Discs, cartridges, bag

Typical applications

Plating and process industry

Features

- Service friendly, ideal cleaning access height
- Magnetic drive pump
- Filter chamber with welded bottom (no seal)
- Discs (thin/thick paper, cloth), cartridges or pleated bag
- All PP construction
- Max. temperature PP 80°C
- Bottom-out or top-out model
- Choice of slurry tank for carbon treatment, mixing and priming
- Unions for rigid piping (PP or CPVC sockets)
- Standard with 3 phase motor, thermal overload switch, lead without plug, pressure gauge, air release and drain valve

Options

- Hose connection
- Contact manometer
- Single open end cartridges



M15-31A-K-PP

Filter Systems series 3

i www.hendor.com

Pump	l/h	kW*	Union (d/DN) In Out	Hose In Out	Type	Chamber	Medium	Slurrytank	Material
Magnetic drive	3000	0,18	32/25 25/20	1 1/4" 1"	M15	31A	K/P		PP-EPDM
	4000	0,18			MX40	32A			
							K/P/D	6 liter 13 liter	
Selection:					MX40	32A	P	S	PP

K = cartridges



Qty x L

31(A)-K = 3 x 10"
32(A)-K = 3 x 20"

P = discs



Qty OD/ID m²

31-P = 37 x 136/32 0,5
32-P = 69 x 136/32 1,0
31A-P = 32 x 136/32 0,4
32A-P = 65 x 136/32 0,9

D = pleated bag



L m²

31-D = 10" 0,4
32-D = 20" 0,7

* For 3-phase motors < 220V the indicated motor will be one size bigger.