



*NOTES:

- THERMAL CUT-OFF DEVICE RATED TO 240 C, MAXIMUM 16.7 A AT 240 VAC
- 2 FT. LEAD WIRE BEYOND CONDUIT SUPPLIED
- WETTED COMPONENTS ARE PTFE TEFLON
- PRIMARY SEALS WITH CHEMRAZ AND TEFLON
- MOUTING BRACKET REMOVED FROM SIDE VEIW FOR CLARITY

UNLESS NOTED TOLERANCES ARE:

0.00	=	±.12
0.000	=	±.125
ANGLES = ±1°		

INCHES (mm)

3rd ANGLE PROJECTION

PROCESS TECHNOLOGY®

7010 LINDSAY DR. MENTOR OH USA
(P) 440-946-9500 (F) 440-974-9561
WWW.PROCESS-TECHNOLOGY.COM

DRAWN BY:	DATE:	DESIGNER:	DATE:
DJO	04/14/05		

DESCRIPTION:	SCALE:
TEFLON IN LINE HEATER WITH MOLDED CHAMBER GENERAL DESCRIPTION (TIHAV-120-208-FC75-050-3)	DRAWING No. 05-0652-0

APPROVED BY:	1:8
	1 OF 1

PCN:	-
MATERIAL:	-

REV.	BY	DATE	DESCRIPTION OF CHANGE
0	DJO	04/14/05	RELEASED

THIS DRAWING IS THE PROPERTY OF PROCESS TECHNOLOGY. IT CONTAINS CONFIDENTIAL INFORMATION AND MAY NOT BE REPRODUCED IN ANY WAY WITHOUT THE PERMISSION OF PROCESS TECHNOLOGY.