


A1+B1+C1 TO POWER IN  
A2+B2+C2 TO POWER OUT

A1+B1 TO LINE 1  
A2+C1 TO LINE 2  
B2+C2 TO LINE 3



RISER \_\_\_\_\_  
LOCATION 'C'

H

— RISER LOCATION 'A'

7

RISER SUPPORT-  
WIRE -OPTIONAL

RISER \_\_\_\_\_  
LOCATION 'C'

H

— RISER LOCATION 'A'

7

- ① PURGE IN FROM SUPPLY TO HEATER  
PRESSURE: 5-10 PSI (.34-.69 BARS)  
RATE: 2-3 SCFH (56.6-85.0 LPH)
- ② PURGE OUT FROM HEATER TO EXHAUST
- ① ① ① HEATER POWER (BLACK LEADS)
- ① ① ① HEATER POWER (BLACK LEADS)
- ⑤ TCO'S (ORANGE LEADS)  
RATED AT 25 AMPS, 240VAC, 240°C
- ⑥
- ⑦ HEATER GUARD AND BOLT OPTIONAL
- ⑧ GROUND WIRE (GREEN) CONNECT ALL TO GROUND.

MODEL No.	3TFFL-6-415-3-S19
DIM 'H'	2"
DIM 'L'	12"
DIM 'W'	12"
DIM 'R'	7'-6"
WIRE LENGTH	12"

0	RELEASED	-	JJC	2/18/03
REV	DESCRIPTION	ECN	BY	CHK DATE
Drawn By:	Title:			
J.J. CLAIR	TRIPLE ELEMENT TFB CONNECTION			
Date:	AND GENERAL LAYOUT			
02/18/03				
Checked By:	SIZE	Drawing No.	REV	SHEET
	A	16-0136	0	1 OF 1
Date:				