

| No. | Description            | Material     | Stock Code |
|-----|------------------------|--------------|------------|
| 1   | LID                    | 316L ST.STL. | 60SI50000  |
| 2   | 2 HIGH GUIDE + CUP     | 316L ST.STL. | 60S002000  |
| 2   | 3 HIGH GUIDE + CUP     | 316L ST.STL. | 60S003000  |
| 2   | 4 HIGH GUIDE + CUP     | 316L ST.STL. | 60S004000  |
| 3   | GUIDE CUP              | 316L ST.STL. | 60S000000  |
| 4   | CENTRE ROD TOP SECT    | 316L ST.STL. | 60S000001  |
| 5   | SPRING + SEAL ASSEMBLY | 316L ST.STL. | 60S000002  |
| 6   | COMPRESSION PLATE      | 316L ST.STL. | 60SI50001  |
| 7   | COMP NUT + WASHER      | 316L/PTFE    | 60S000003  |
| 8   | COMP NUT WASHER        | PTFE         | 60S00000T  |
| 9   | TOP GASKET             | E.P.         | 60SI5000E  |
| 9   | TOP GASKET             | VITON        | 60SI5000V  |
| 10  | CLAMP                  | 304 ST.STL.  | 60SI50002  |
| 11  | CLAMP TEE BAR          | 316L ST.STL. | 60S000022  |
| 12  | DRAIN CAPS             | 316L ST.STL. | 60S000006  |
| 13  | VENT CAP               | 316L ST.STL. | 60S000005  |
|     |                        |              |            |
|     |                        |              |            |
|     |                        |              |            |
|     |                        |              |            |
|     |                        |              |            |
|     |                        |              |            |

| Connection Options      | Dim 'F' |
|-------------------------|---------|
| 4" ANSI B16.5 150 lb SO | 520     |
| DN100 DIN 2633          | 610     |
| 4" TRI-CLAMP            | 494     |
| NW100 DIN 11851 'M'     | 560     |
| 4" RJT 'M'              | 515     |
| 4" IDF 'M'              | 510     |
|                         |         |

| DESIGN PRESSURE Bar g |     | DESIGN TEMPERATURE °C |      |
|-----------------------|-----|-----------------------|------|
| LIQUID                | GAS | MIN.                  | MAX. |
| 6                     | N/A | 0                     | 110  |

| Model          | No. of Cartridges | Max Operating Conditions Bar.g and °C | Materials of Construction | Connection Size and Type | Volume (litres) | Dry Weight (kg) | Dimension (mm) |     |     |     |      |
|----------------|-------------------|---------------------------------------|---------------------------|--------------------------|-----------------|-----------------|----------------|-----|-----|-----|------|
|                |                   |                                       |                           |                          |                 |                 | A              | B   | C   | D   | E    |
| 611520AN40CIEE | 15 x 20"          | SEE TABLE                             | 316 ST.STL.               | 4" BS4504 PN16 RF/SO     | 77.5            | 57.4            | 953            | 320 | 150 | 520 | 500  |
| 611530AN40CIEE | 15 x 30"          | SEE TABLE                             | 316 ST.STL.               | 4" BS4504 PN16 RF/SO     | 102.0           | 64.8            | 1208           | 320 | 150 | 520 | 750  |
| 611540AN40CIEE | 15 x 40"          | SEE TABLE                             | 316 ST.STL.               | 4" BS4504 PN16 RF/SO     | 126.5           | 72.2            | 1463           | 320 | 150 | 520 | 1000 |
|                |                   |                                       |                           |                          |                 |                 |                |     |     |     |      |

|                       |  |                                                           |  |  |  |                 |  |  |        |  |  |
|-----------------------|--|-----------------------------------------------------------|--|--|--|-----------------|--|--|--------|--|--|
| <b>www.hendor.com</b> |  | <b>F-152/153/154-HK-SS</b><br>FOR D.O.E CODE `O` ELEMENTS |  |  |  |                 |  |  |        |  |  |
|                       |  |                                                           |  |  |  | Drg. No. 6115-I |  |  | Rev. 2 |  |  |

